# CAMSO BHL 573

BACKHOE
LOADERS

## A SMOOTH RIDE WITH ENHANCED TRACTION

A smooth ride and effective steering in both on and off-road applications. Provides improved off-road traction and sidewall impact resistance

## PERFORMANCE

TIRE LIFE

PUNCTURE RESISTANCE

TRACTION

CAMSO
CONSTRUCTION

# CAMSO BHL 573



### ENGINEERED TREAD DESIGN

- Provides a smooth ride and effective steering

### SELF-CLEANING STEPPED TREAD

- Maximizes cleanout for improved off-road traction

### IMPACT GUARD SIDEWALL DESIGN

- Deflects debris to better protect sidewalls and reduce stress cracking

### HIGH LUG-TO-VOID RATIO

- Provides excellent durability and tread impact resistance

| TIRE SIZE | PR | TL/ TT | RIM SIZE | | ACTUAL TIRE DIMENSIONS | | | LOAD INDEX | SPEED SYMBOL | APPLICATION | INFLATION PRESSURE | MAXIMUM TIRE LOAD [kg] [lb] | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | Recom-mended | Alternative | O.D. [mm] [in] | O.W. [mm] [in] | O.T.D. [mm] [32nd] | | | | [bar] [PSI] | Static | 10 km/h 6 mph | 15 km/h 9 mph | 20 km/h 12.5 mph | 25 km/h 16 mph | 30 km/h 19 mph | 35 km/h 22 mph | 40 km/h 25 mph |
| **9.00-16** | 16 | TT | 6.50H (SDC) (6.00G) | 6.00G | 920 | 274 | 21 | 137 | A6 | Free rolling | 7.25 | 3795 | 2965 | 2785 | 2620 | 2460 | 2300 | 2185 | 2070 |
| | | | | | *36.2* | *10.8* | *26* | | | | *105* | *8365* | *6535* | *6140* | *5775* | *5425* | *5070* | *4815* | *4565* |
| | | | | | 920 | 274 | 21 | | | Drive | 7.25 | 5405 | 2965 | 2785 | 2620 | 2460 | 2300 | 2185 | 2070 |
| | | | | | *36.2* | *10.8* | *26* | | | | *105* | *11915* | *6535* | *6140* | *5775* | *5425* | *5070* | *4815* | *4565* |

AUTHORIZED DISTRIBUTOR: