

CAMSO BHL 753



BACKHOE
LOADERS



DURABILITY MEETS RIDE QUALITY

Thoroughly designed to ensure even tread wearing and reduce vibrations. Comfort and long tire life combined.

PERFORMANCE

TIRE LIFE




PUNCTURE RESISTANCE



TRACTION



CAMSO BHL 753



NON-DIRECTIONAL TREAD PATTERN WITH HIGH LUG-TO-VOID RATIO

- Ensures even tread wearing for greater durability

OPTIMIZED, CONTINUOUS-CONTACT TREAD PATTERN

- Significantly reduces vibration for improved ride quality



NON-DIRECTIONAL TREAD PATTERN WITH HIGH LUG-TO-VOID RATIO

- Protects against tread impacts and punctures

TAPERED TREAD LUGS

- Improves lug stability for even wearing

TYRE SIZE	ALTERNATIVE SIZE	PR	O.T.D.	LOAD INDEX	SPEED SYMBOL	INFLATION PRESSURE
			[mm] [32 nd inch]			[bar] [PSI]
12-16.5 NHS	300/70-16.5; 305/70-16.5	12	18 (23)	145	A2	5.5 (80)
12.5/80-18 IMP	320/80-18	12	23 (29)	142 - 129	A8	3.7 (54)
12.5/80-18 IMP	320/80-18	14	23 (29)	146 - 134	A8	4.3 (62)
19.5L-24 IND	500/70-24	12	25 (31)	151	A8	2.3 (33)
18.4-26 IND	480/80-26	12	25 (31)	156	A8	2.5 (36)
16.9-28 IND	440/80-28	12	28 (35)	152	A8	2.6 (38)

MASSIVE UNDERTREAD CONNECTING CENTER LUGS

