

# CAMSO SL 63



TELEHANDLERS



## MULTI-SURFACE STABILITY AND PERFORMANCE

Performs well both off-road and on hard surfaces. Engineered with durability and traction in mind, it also delivers superior side impact resistance and stability in heavy-duty applications.

## PERFORMANCE

TIRE LIFE




PUNCTURE RESISTANCE



TRACTION



# CAMSO SL G3



### OPTIMIZED LUG-TO-VOID RATIO

- Provides excellent traction for mixed and hard surface applications

### EXTRA-DEEP NON-DIRECTIONAL TREAD PATTERN

- Optimizes durability and traction on mixed and hard surfaces



### FLATTER TREAD PROFILE

- Resists tread crowning for even wearing



### HEAVY-DUTY SIDEWALL CONSTRUCTION

- Provides superior side impact resistance and stability

TYRE SIZE	ALTERNATIVE SIZE	PR	O.T.D.	SERVICE TYPE	LOAD INDEX	SPEED SYMBOL	INFLATION PRESSURE
			[mm] [32 <sup>nd</sup> inch]				[bar] [PSI]
370/75-28	N/A	14	28 (35)	Earthmover	149	B	3.25 (47)
				Loader-Dozer	167	A2	5.00 (73)
400/75-28	N/A	16	28 (35)	Earthmover	155	B	3.50 (51)
				Loader-Dozer	173	A2	5.25 (76)

**CAMSO SL G2**  
Lug-to-void: 45.7%

**CAMSO SL G3**  
Lug-to-void: 50%



The higher lug-to-void ratio offered by Camso SL G3 provides significantly **greater durability and stability with improved ride quality**. Tread impact resistance is also enhanced and thus operators can expect reduced downtime due to flat tires.

